



Environmental Data Sheet For Lounge Seating

Part 1. Corporate Information

| | |
|----------------------------------|--|
| Product: | Visit Upholstered |
| Manufacturer: | IDEON 14950 Valley View Ave. La Mirada, CA 90638 |
| Customer Service Contact: | Kanani Bahena V.P. Customer Support 1-714-995-4800 Ext. 348 kbahena@exemplis.com |
| Engineering Contact: | Andy Paskin V.P. Engineering 1-714-995-4800 Ext. 426 apaskin@exemplis.com |

Part 2. Material Content Description

| Material | Percent by Weight | Recycled Content ¹ | End of Life Management |
|--|-------------------|--------------------------------------|------------------------|
| Steel: rod, tubing cold/hot rolled flat stock | 0.0% | 60% PC | Recycle where possible |
| Wood Products | 78.6% | 0% From Rapidly Renewable Forests | Recycle where possible |
| Polyurethane foam | 15.5% | 0% PC | Recycle where possible |
| Fabrics, Natural / Synthetic | 4.9% | 0% - 100% ² | Recycle where possible |
| Compressed Particle Board | 0.0% | 60% PC | Recycle |
| Miscellaneous | 1.0% | 60% PC | Recycle where possible |
| Total Post Consumer Recycled Content | .6% - 5.5% | | |

PI = Post Industrial or Pre Consumer recycled content PC = Post Consumer recycled content

¹Values are based on the recycled content of the total chair weight and the specific chair style.

² Range based on specific fabric brand and type.

Comments:

- The Exemplis Company complies with the Federal Trade Commission's Part 260 *Guide for the Use of Environmental Marketing Claims*.
- The Exemplis Company encourages bulk packaging and wraps products where appropriate.
- Product recyclability depends on local programs.

Part 3. Manufacturing Process Description

- ▶ Wood components are assembled using mechanical fasteners and water based glue. The arms, back and seat use a water based adhesive to attach the foam to the wood pieces.
- ▶ Steel tubing supports add strength and support to the underneath side of the chair
- ▶ A polyethylene bag covers the chair, and is placed in a corrugated cardboard carton

Part 4. Indoor Air Emissions

| Test Methodology: CA 01350 | Date of Test: 12/2007 | | |
|--|--|--|------------|
| Test Location: Greenguard Certification Laboratory, Atlanta, Georgia | | | |
| Standard | Compound | Criteria | Acceptable |
| State of California | Formaldehyde | 0.025 ppm | Yes |
| Indoor Air Quality and Collaborative for High Performance Schools (CHPS) Section 01350 | TVOC | 0.250 mg/m ³ | Yes |
| | Meets 1/10th TLV for emitting VOC's | | Yes |
| | Meets any regulated primary or secondary National Ambient Air Quality Standard (NAAQS) | | Yes |
| U.S. Environmental Protection Agency (EPA) | Formaldehyde | 0.025 ppm | Yes |
| | TVOC | 0.250 mg/m ³ | Yes |
| | Total Aldehydes | 0.05 ppm | Yes |
| | 4-phenylcyclohexene | 0.0065 mg/m ³ | Yes |
| | Title VI of the 1990 Clean Air Act Amendments. (CFC's & HCFCs) | This product does not contain and is not manufactured with ozone | |
| U.S. Occupational Safety & Health Administration (OSHA) | Formaldehyde | 0.10 ppm | Yes |

Green Guard Certification No. 90059-31

Notes: Additional data may be available upon request.

OSHA - (29 CFR) 1910.1048